DATA CENTER SOLUTIONS

Floor Mount Cabinets – Perforated Door



Product Overview

Alston Systems offers an entire range of Data cabinets such as server cabinets, wall / floor mount cabinets, power distribution units, and IP based PDUs, UPS etc., towards a Data Center Facility Solution. Additionally, Alston Systems has physical security to the server cabinet access by IP based biometric handle locks. Protection of physical assets is regarded to be as important as protecting the data stored or processed on those active equipment's. Accessories like fans, castors and levelling feet come with the floor mount cabinet pack. Additional accessories like fix shelf, keyboard tray, LED light, blank cover, cable management and numeric/biometric access control systems can be ordered along with the standard pack.

Features

- Welded frame with high intensity.
- Blue Zinc mounting profiles, free of static.
- Bottom with cable entrance, optional cover to close.
- Exquisite design with precision measurement and craftsmanship.
- Side doors with locks for protection & advanced moon shaped lock.
- Adjustable feet and heavy duty castors are available simultaneously.
- Cable entry on the top cover and bottom panel with adjustable sizes.
- Hexagonal rectangular high-density vented front door(patent) & rear door enabled equipment protection, verification and reliable operation with turning angle above 120 degree and ventilation rate above 71 %.

Material	SPCC Cold Rolled Steel Thickness of Steel, Mounting profile : 2.0mm; Tray: 2.0mm ; Mounting angle : 1.5mm				
Surface Finish	Frame: Degreasing, Phosphoric, Powder Coat				
Surface Thisi	Others: Degreasing, Phosphoric, Powder Coat				
Load Capacity	Static Loading: 1000kg(with adjustable feet)				
Degree of Protection	IP 20				
Standards	Compliant with ANSI/EIA RS-310-D, DIN 41497 Part1, IEC297-2 DIN41494 Part7 GB/TB3047, 2-92				
Body Color	Black (RAL 9004) / Grey (RAL 7035)				

Ordering Information

Model	Part Number	Width	Depth	Height	Model	Part Number	Width	Depth	Height
18U	443180663	600	600	986	37U	443370663	600 800	600	1833
	443180683		800			443370683		800	
	443186103		1000			443376103		1000	
	443180883	800	800			443370883		800	
	443188103		1000			443378103		1000	
22U	443220663	600	600	1166	42U	443420663	600	600	2055
	443220683		800			443420683		800	
	443226103		1000			443426103		1000	
	443220883	800	800			443426123		1200	
	443228103		1000			443420883	800	800	
27U	443270663	600	600	1388		443428103		1000	
	443270683		800						
	443276103	800	1000		47U	443428123	600	1200	2277
	443270883		800			443470663		600	
	443278103		1000			443470683		800	
32U	443320663	600 800	600	1610		443476103		1000	
	443320683		800			443476123		1200	
	443326103		1000			443470883		800	
	443320883		800			443478103		1000	
	443328103		1000			443478123		1200	

© 2022 Alston Systems Inc. All Rights Reserved.

All information is subject to change without notice since Alston Systems reserves the rights to change its products as progress in engineering & manufacturing methods or other circumstances may warrant.